

With Safety.

## Datasheet Breathing filter 205 A2P3 R

Designation: Respiratory protection insert filter with bayonet

connection

Filter 205 A2P3 R

Combination filter according to DIN EN 14387

Description: Cylindrical housing with asymmetrical bayonet

connection for connection to a double filter mask

Article-Number: 126025 (packaging unit 4 pieces)

Application: DUPLA, for protection against organic gases and vapors,

and against particles (R = Reusable - reusable against particles)

Standards: DIN EN 133 Respiratory protective devices - Classification

DIN EN 14387 Respiratory protective devices - Gas filters and

combination filters

Identification color: Brown-white (adhesive label)

Materials: Filter housing with bayonet connection

Filter medium gas Filter medium particles Polypropylene, blue Activated carbon Glass/cellulose fiber

Dimensions: Diameter approx. 85 mm

Height approx. 65 mm

Weight: approx. 135 grams per piece

Inhalation resistance: < 2.6 mbar at 30 l/min constant air flow

< 9.8 mbar at 95 l/min constant air flow

Handling: Unpack the filter immediately before use (remove the foil)

and connect to the mask (follow the arrows)

Main application: Designed for areas contaminated by dust and solvent vapors. The design

guarantees the filtration of organic gases and vapors (boiling point > 65°C)

and a particle separation efficiency > 94.95%.

Service life: The service life of combination filters depends on several factors

such as concentration of harmful gases, ambient temperature, humidity, work severity, posture, etc. and therefore cannot be determined in advance.

Opened filters must be replaced after 6 months at the latest.

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.



With Safety.

## Datasheet Breathing filter 205 A2P3 R

Application limits: according to technical rules for hazardous substances TRGS 900

"Occupational exposure limits"

with half/quarter mask (gas filter): 30 times the occupational

exposure limit value

with half/quarter mask (particle filter): 30 times the occupational

exposure limit value

Maximum permissible

Gas concentration: of gas filter class 2 (A2, B2, E2, K2) =

5,000 ml/m<sup>3</sup>

Instructions for use: The use of respiratory filters requires a basic knowledge of the function and

handling of respiratory protective devices. Information on this can be found in the trade association regulations and rules, in particular in DGUV Rule

the trade association regulations and rules, in particular in DGUV R

112-190.

The use of respiratory protective devices generally means additional strain for

the person wearing the respiratory protective device.

Most respiratory protective devices require occupational health screening in accordance with the "Ordinance on Occupational Health Care" (ArbMedVV).

Damaged filters must not be used.

Rules / regulations: Regulation (EU) 2016/425 on personal protective equipment

PPE Usage Ordinance (PSA-BV)

Ordinance on Occupational Health Care (ArbMedVV)

BGV A1 Employer's Liability Insurance Association Regulation for Safety and Health at Work - Accident Prevention Regulation - Principles of Prevention

DGUV Rule 112-190 Employer's liability insurance association rules for safety

and health at work - "Use of respiratory protective devices"

Hazardous Substances Ordinance (GefStoffV) with associated Technical Rules for Hazardous Substances (TRGS), in particular TRGS 402 "Determination and assessment of hazards during activities involving hazardous substances: Inhalative exposure" and other technical rules for

hazardous substances.

Order details: Article-Number Description

126025 Combination filter 205 A2P3 R

914000 DUETTA half mask

929105 Coarse dust pre-filter 35/70

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.