

## Datasheet Compressed air supplying hose DZS 9

Designation:	Compressed air supply hose DZS 9 AK 2, 5 m	
Description:	<p>The DZS 9 compressed air supply hose conducts the breathing air from the tapping point to the compressed air hose device.</p> <p>The hose is available in various individual lengths so that the length actually required in individual cases can also be assembled from hoses connected in series. Physiologically safe (food hoses). No hazardous substances that affect the breathing air are used in the manufacture of the hose.</p> <p>Each hose is equipped with an automatic breathing air coupling and a corresponding AK2 plug-in nipple.</p>	
Article-Number:	941114	
Application:	Hoses are available in various individual lengths. If required, several hoses can be combined to achieve a greater hose range (maximum length 50m).	
Standards:	DIN EN 14593-1	Respiratory protective devices - Compressed airline breathing apparatus with demand valve
	DIN EN 14594	Respiratory protective devices - Compressed airline breathing apparatus with continuous air flow
Identification color:	Breathing hose with black outer cover and longitudinal blue stripe	
Materials:	Outer cover	Ethylene-propylene-diene rubber
	Reinforcement	Polyvinyl alcohol
	Breathing air coupling	Nickel-plated
	Plug nipple	Nickel-plated
	Hydraulic connection with stainless steel crimp sleeve	
Dimension:	Inner diameter 9.5 mm Outer diameter 19.5 mm Available lengths 5 m, 10 m, 15 m, 20 m, 30 m, 40 m, 50 m	
Bending radius:	78 mm	
Weight:	approx. 1.43 kg	
Operating pressure:	10 bar	
Burst pressure:	> 60 bar	
Resistance:	Good resistance to ageing and ozone. Ideal for use when cleaning tanks etc. or when the outer surface of the hose is exposed to adverse conditions.	



Revision 08.2023 – Errors and omissions excepted. All data are non-binding guide values.

**BartelsRieger Atemschutztechnik GmbH**

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de  
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt

## Datasheet Compressed air supplying hose DZS 9

Marking:	BARTELS RIEGER - DZS 9 - A T E M L U F T - EN 14593-1 / EN 14594 (CLASS B) H S F - mm-jjjj - batchno
Heat resistance:	"H" according to EN 14593-1 / EN 14594, -30° C to +120° C
Buckling resistance:	according to EN 14593-1 / EN 14594
Dimensional stability:	according to EN 14593-1 / EN 14594
Flexibility:	according to EN 14593-1 / EN 14594
Tensile strength:	according to EN 14593-1 / EN 14594; >1,000 N with integrated couplings couplings
Antistatic:	"S" according to EN 14593-1 / EN 14594; 10 <sup>3</sup> - 10 <sup>8</sup> Ohm; with integrated couplings
Flame resistant:	"F" according to EN 14593-1 / EN 14594

Revision 08.2023 – Errors and omissions excepted. All data are non-binding guide values.

**BartelsRieger Atemschutztechnik GmbH**

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | [mail@bartels-rieger.de](mailto:mail@bartels-rieger.de) | [www.bartels-rieger.de](http://www.bartels-rieger.de)  
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt