

Datasheet

Portable breathing air supply

Designation:	Portable breathing air supply TAV without breathing air cylinders	
Description:	Mobile breathing air supply	
Article-Number:	841022	
Material:	Case	Aluminum
Application:	<p>The TAV is used to supply breathing air to compressed air hose devices with regulators.</p> <p>Calculated air supply when using a compressed air breathing apparatus with regulator:</p> <p>Low breathing: 50 l/min = approx. 76 min; High breathing: 100 l/min = approx. 38 min</p>	
Dimensions:	700 x 500 x 180 mm	
Weight:	with cylinders approx. 27 kg	
Breathing air supply:	Two 6.8 l / 300 bar breathing air cylinders (up to 3,800 liters of breathing air supply)	
Medium pressure outlets:	AK2 coupling	
Filling and feed connection:	300 bar	
Medium pressure gauge:	0-16 bar	
High pressure gauge:	0-400 bar	
Warning device:	sounds in the panel at a residual pressure of approx. 35 ± 5 bar	
Pressure reducer:	1x DM 1900	



Revision 02.2024 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt