

Datasheet

Cylinder trolley AIR2GO mini



With Safety.

BR Article No.:	202003
Article-Name:	AIR2GO mini
Article Type:	Mobile breathing air supply
Type of construction:	welded stainless steel tube construction
Dimensions (LxWxH):	60 cm (80 cm with folded out protection bar) x 60 cm x 125 cm
Weight:	without compressed air cylinders approx. 50 kg



Cylinder trolley with 2-wheel safety chassis made of stainless steel, with screwed-on crane eye for height loading.

Manual hose reel made of stainless steel, equipped with compressed air supply hose DZS 9 (50 m length), electrically conductive.

Breathing air supply: holder for two pressurized gas cylinders for breathing air à 6-9 l/300 bar stable, height-adjustable push bar

Pneumatic panel - clearly arranged and user-friendly, equipped with:

- DM 1900 pressure reducer with residual pressure warning direction (optionally intermittent) and two AK2 center pressure tapping couplings
- High-pressure manifold block with filling and feed connection G 5/8, 300 bar and flexible HP connecting hoses for connection to the compressed gas cylinders for breathing air
- High and medium pressure manometer 0-400 bar / 0-16 bar System vent valve

Revision 09.2018 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt