

Datasheet Cylinder trolley Air2go mini

Designation:	Air2go mini cylinder trolley
Description:	Mobile breathing air supply Cylinder trolley with 2-wheel safety chassis made of stainless steel, with bolted crane lifting eye for loading at height. Manual hose reel made of stainless steel, equipped with DZS 9 compressed air supply hose (50 m long), electrically conductive.
Article-Number:	202003
Design:	Welded stainless steel tube construction
Dimensions:	Height: approx. 1,25m Width: approx. 60 cm Depth: approx. 60 cm (80 cm with folded out protective bar)
Weight:	without compressed air cylinders approx. 50 kg
Breathing air supply:	Holder for two compressed air cylinders For 6-9 l/300 bar breathing air Sturdy, height-adjustable push handle



Pneumatic control panel - clearly laid out and user-friendly, equipped with

- DM 1900 pressure reducer with residual pressure warning direction (optionally intermittent) and two AK2 medium-pressure tapping couplings
- High-pressure manifold block with filling and feed connection G 5/8, 300 bar and flexible high-pressure connection hoses for connection to the compressed gas cylinders for breathing air
- High and medium pressure gauges 0-400 bar / 0-16 bar
- System vent valve

Revision 09.2018 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt