

With Safety.

Datasheet Full face mask BRK820G

Designation:	Full face mask BRK 820 G EN 136 Class 3 with round thread connection (EN148-1) Breathing connection in normal pressure version according to DIN EN 136 for respiratory protective devices (personal protective equipment)	
Description:	Mask body made of rubber compound, inner mask with control valves, panoramic visor with two-part plastic frame, connection piece with inhalation valve, two exhalation valves and speaking membrane, 5-point harness with clamp buckles, carrying strap	
Article-Number:	111208	
Use:	 In conjunction with breathing filter as filter device In conjunction with hose device (fresh air / compressed air) or container device (compressed air breathing apparatus) as an insulating device 	
Function:	The (aspirated) inhaled air flows through the inhalation valve and enters the inner mask through the control valves between the inner mask and the visor. The exhaled air passes through two exhalation valves directly into the open air.	
Materials:	Mask body, strapEthylene-propylene-diene rubberInner maskThermoplastic elastomerTensioning frame for lensPolyamideConnection piecePolyphenylene etherSpeech membrane, stainlesssteel screwsThreaded sleeves in tensioning frame and strapBrassCarrying strapPVCSealing ring, valve disksRubberWindowPolycarbonateSurface hardened	
Dimensions:	approx. 230 x 175 x 125 mm (dimensions of the folding box)	
Weight:	approx. 580 g	
Inhalation resistance:		
	< 2.5 mbar at 25 x 2 l/min (mbar)	

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt



With Safety.

Datasheet Full face mask BRK820G

Storability:	The materials used for the BRK 820 G full face mask have excellent ageing resistance, which means that no special measures are required for storing the masks. Nevertheless, we recommend storing new masks in their original packaging in well-ventilated depots and away from any sources of heat. The masks should be stored at temperatures between -20 and 50 °C. Ready-to-use masks should be protected from dust, light, chemical vapors and heat sources and stored in closed cabinets.
Instructions for use:	The use of respiratory filters requires a basic knowledge of function and handling of respiratory protective devices. Information can be found in the regulations and rules of the employers' liability insurance association rules, in particular DGUV Rule 112-190. The use of respiratory protective devices generally means additional strain on the person wearing the breathing apparatus. Most respiratory protective devices make the occupational health screening in accordance with the "Ordinance on Occupational Health Care" (ArbMedVV) is required. Damaged filters must not be used.
Rules / regulations:	 Regulation (EU) 2016/425 on personal protective equipment PPE Usage Ordinance (PSA-BV) Ordinance on Occupational Health Care (ArbMedVV) BGV A1 Employer's Liability Insurance Association regulation for safety and health at work - Accident Prevention Regulation - Principles of Prevention DGUV Rule 112-190 Employer's liability insurance association rules for safety and health at work - "Use of respiratory protective devices" Hazardous Substances Ordinance (GefStoffV) with associated technical rules for Hazardous Substances (TRGS), in particular TRGS 402 "Determining and Assessment of hazards during activities involving hazardous substances: Inhalative Exposure" and other technical rules for hazardous substances.

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt



filters

With Safety.

Datasheet Full face mask BRK820G

Article number	Description
111208	Full face mask 820 G
920000	Gas filter 19A
920001	Gas filter 19B
920002	Gas filter 19E
920003	Gas filter 19K
924000	Combination filter 39 ASt
924002	Combination filter 39 BSt
924003	Combination filter 39 ESt
924004	Combination filter 39 KSt
924100	Combination filter 40 Ast
924110	Combination filter 45 ABSt
929005	Filter holder 5570/35
929006	Filter holder 5570/70
929105	Coarse dust pre-filter 35/70
922300	Particle filter 24 P2
922350	Particle filter 25 P3
922404	Particle filter 30 P3
200525	Particle filter 30 P3 Plus
920600	Gas filter 66 A
920601	Gas filter 66 B
920603	Gas filter 66 K
920650	Gas filter 67 ABEK
924300	Combination filter 80 Ast
924301	Combination filter 80 BSt
924350	Combination filter 80 ABEKSt
924400	Combination filter 81 ASt
924406	Combination filter 81 ABSt
924450	Combination filter 81 ABEKSt
924452	Combination filter 81 ABEKHgSt
920850	Gas filter 84 AX
920851	Gas filter 84 ABEK
924702	Combination filter 86 AXSt
924701	Combination filter 86 ABEKSt
924703	Combination filter 86 ABEKHgSt
924700	Special filter 86 NOSt
925003	Fire brigade training filter Rd 40
925005	Fire brigade training filter M45x3
929105	Coarse dust pre-filter 35/70
020100	
111704	Wall container for full face mask incl. one filter
111705	Wall container for two full face masks incl. two
111702	Carrying case FE for BRK 820
173009	Clear Pilot anti-fog spray
173008	Clear Pilot GEL anti-fogging agent
173007	Anti-fogging agent FLUID Clear Pilot
111712	Prescription mask frame

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Order details:

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt