

With Safety.

Datasheet Breathing filter 66 K

Designation:	Respiratory protection screw filter K2 Gas filter to DIN EN 14387 - filter type K - filter class 2 – as part of a respiratory protective device to DIN EN 133 – filter device		
Description:	Cylindrical housing with round thread connection to DIN EN 148-1 (external thread Rd 40 x 1/7) Air inlet side with profiled perforated disk		
Article-Number:	920603		
Application:	In conjunction with breathing connection - full face masks (DIN EN 136) or half masks (DIN EN 140) with round thread connection - For protection against ammonia		
Standards:	DIN EN 133 DIN EN 148-1	Respiratory protective devices Respiratory protective devices breathing connections - Round	- Threads for
	DIN EN 14387	connection Respiratory protective devices and combination filters	- Gas filters
Identification color:	green (adhesive label)		
Materials:	Housing, perforated disks Filter medium Non-woven discs Sealing foil	Aluminum alloy Activated carbon Polypropylene Polypropylene	
Dimensions:	Diameter approx. 91mm Height approx. 68mm		
Weight:	approx. 225 grams		
Inhalation resistance:	< 1.4 mbar at 30 l/min constant air flow < 5.6 mbar at 95 l/min constant air flow		
Storability:	6 years - from date of manufacture (protected from cold, heat and moisture)		
Handling:	Only open the filter immediately before use and screw firmly into the connector of the mask.		
Main application:	Ammonia		
Service life:	The service life of gas filters depends on several factors such as concentration of harmful gases, ambient temperature, air humidity, work intensity, posture, etc. and therefore cannot be determined in advance. Opened filters must be replaced after 6 months at the latest.		

Revision 11.2023 - Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt



With Safety.

Datasheet Breathing filter 66 K

Application limits:	according to technical rules for hazardous substances TRGS 900 "Occupational exposure limits" with half/quarter mask: 30 times the occupational exposure limit value with full face mask: 400 times the occupational exposure limit value Maximum permissible Gas concentration: of gas filter class 2 (A2, B2, E2, K2) = 5,000 ml/m ³		
Instructions for use:	The use of respiratory filters requires a basic knowledge of the function and handling of respiratory protective devices. Information on this can be found in the trade association regulations and rules, in particular in DGUV Rule 112-190. The use of respiratory protective devices generally means additional strain for the person wearing the respiratory protective device. Most respiratory protective devices require occupational health screening in accordance with the "Ordinance on Occupational Health Care" (ArbMedVV). Damaged filters must not be used.		
Rules / regulations:	Regulation (EU) 2016/425 on personal protective equipment PPE Usage Ordinance (PSA-BV) Ordinance on Occupational Health Care (ArbMedVV) BGV A1 Employer's Liability Insurance Association Regulation for Safety and Health at Work - Accident Prevention Regulation - Principles of Prevention		
	DGUV Rule 112-190 Employer's liability insurance association rules for safety and health at work - "Use of respiratory protective devices"		
	Hazardous Substances Ordinance (GefStoffV) with associated Technical Rules for Hazardous Substances (TRGS), in particular TRGS 402 "Determination and assessment of hazards during activities involving hazardous substances: Inhalative exposure" and other technical rules for hazardous substances.		
Order details:	Article number 9200603	Description Gas filter 66 K	
	111200 111201 111208 111400 913503 913510 912500BL	Full face mask BRK 820 Full face mask BRK 820 V Full face mask BRK 820 G Full face mask TR 2002 CL3 Half mask 620 N Half mask 620 S Half mask 600	
	111704 111705	Wall container for full face mask including one filter Wall container for two full face masks including two filters	
Revision 11.2023 – Errors and	111703 d omissions excepted. All da	Carrying case B78 for one full face mask and one filter ta are non-binding guide values.	

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt