

Datasheet AirSafe Mini

Designation: Mobile breathing air supply AirSafe Mini

Description: Breathing air case with emergency air supply
Mounted in sturdy transport case
Breathing air inlet and outlet (coupling system AK2) are accessible from the outside of the case. The pressure of the supplied breathing air (max. 6 bar) is monitored by the control unit of the back-up system monitored.

If the pressure falls below 3.5 bar, the system switches to the emergency air supply without interruption and an audible alarm sounds.

The pneumatic components are easily accessible, the compressed air cylinder is secured with a fastening clip and is easy to replace. secured with a fastening clip and is easy to replace.



Article-Number: 202837

Materials: Case Impact-resistant and acid-resistant polymer
(waterproof and dustproof case)

Dimensions: 55 x 35 x 25cm

Emergency air supply: One 2l / 300 bar breathing air cylinder with pressure reducer and automatic changeover valve

Pressure reducer: DM 1900

Breathing air in- and outlet: AK2 coupling system is accessible from the outside of the case. Breathing air inlet with protective screen.

Revision 02.2024 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de

Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt