

Datasheet Breathing filter 86 ABEKHgSt/ Ü

Designation:	Breathing protection screw filter ABEK2Hg-P3 R D Thread M 45 x 3 Special filter according to DIN EN 14387 Filter type/class A2 B2 E2 K2 Hg- P3 R D Combination filter as part of a respiratory protective device according to DIN EN 133 - Filter device	
Description:	Cylindrical housing with threaded connection M 45 x 3 according to DIN EN 148-3	
Article-Number:	924715	
Application:	In conjunction with breathing connection - full face masks (DIN EN 136) with threaded connection M 45 x 3 - for protection against organic gases and vapors with boiling point above 65°C, against inorganic gases and vapors e.g. chlorine, hydrogen sulfide (hydrogen sulfide), hydrogencyanide (hydrogen cyanide, hydrogen cyanide) - not against carbon monoxide – against sulfur dioxide, hydrogen chloride (hydrogen chloride), against ammonia, against mercury vapor and against particles R = Reusable - reusable against particles D = particularly resistant to clogging by dust (storage test with dolomite dust in accordance with EN 143)	
Standards:	DIN EN 133 DIN EN 148-3 DIN EN 14387	Respiratory protective devices - Classification Respiratory protective devices - Threads for breathing connections Threaded connection M45 X 3 Respiratory protective devices - Gas filters and combination filters
Identification colors:	brown - grey - yellow - green - red - white (adhesive label)	
Materials:	Housing, perforated disks Filter medium Non-woven discs Sealing foil	Aluminum alloy Activated carbon and glass/cellulose fiber Polypropylene Polypropylene
Dimensions:	Diameter approx. 108 mm Height approx. 104 mm	
Weight:	approx. 360 grams	
Inhalation resistance:	< 2.6 mbar at 30 l/min constant air flow < 9.8 mbar at 95 l/min constant airflow	
Filter flow rate:	Sodium chloride test at 95 l/min: < 0.05 % Kerosene oil test at 95 l/min: < 0.05 %	
Storability:	6 years - from date of manufacture (protected from cold, heat and moisture)	



Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt

Datasheet Breathing filter 86 ABEKHgSt/ Ü

Handling:	Only open the filter packaging immediately before use and screw firmly into the connector of the mask.
Main application:	Organic gases and vapors (boiling point > 65°C) and against inorganic gases and vapors e.g. chlorine, hydrogen sulphide (hydrogen sulphide), hydrogencyanide (hydrogen cyanide, hydrogen cyanide) as well as against sulphur dioxide, hydrogen chloride (hydrogen chloride), ammonia, mercury vapor and particles.
Service life:	The service life of combination filters depends on several factors such as the concentration of the harmful gases, ambient temperature, humidity, severity of work, posture, etc. and therefore cannot be determined in advance. Opened filters must be replaced after 6 months at the latest.
Application limits:	<p>according to technical rules for hazardous substances TRGS 900 "Occupational exposure limits"</p> <p>with full-face mask (particle filter): 400 times the occupational exposure limit value</p> <p>with full face mask (gas filter): 400 times the occupational exposure limit value</p> <p>Maximum permissible Gas concentration: of gas filter class 2 (A2, B2, E2, K2) = 5,000 ml/m³</p>
Instructions for use:	<p>The use of breathing filters requires a basic knowledge of the function and handling of respiratory protective devices. Information on this can be found in the trade association regulations and rules, in particular in DGUV Rule 112-190.</p> <p>The use of breathing apparatus generally means additional stress for the person wearing the breathing apparatus.</p> <p>Most respiratory protective devices require occupational health screening in accordance with the "Ordinance on Occupational Health Care" (ArbMedVV).</p> <p>Damaged filters must not be used.</p> <p>In ATEX areas, these respiratory protection filters can be used in potentially explosive atmospheres in zones 1, 21, 2 and 22 if the following requirements are observed:</p> <ul style="list-style-type: none"> • The respiratory protection filters must be earthed via a dissipative mask and via the earthing of the wearer with a leakage resistance <108 Ω. • The respiratory protection filters must not be used in areas where highly charge-generating processes are to be expected. • In the presence of an explosive atmosphere, the respiratory protection filters may only be worn on the face mask and not on the belt. • The permissible ambient temperature must not exceed a value of 70 °C, assuming a temperature increase of 10 K at the parts in contact with an explosive atmosphere during normal operation and also in the event of a fault (zone 1 or 21) or during normal operation (zone 2 or 22) due to the activated carbon filter

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt

Datasheet

Breathing filter 86 ABEKHgSt/ Ü

Rules / regulations:

Regulation (EU) 2016/425 on personal protective equipment
PPE Usage Ordinance (PSA-BV)
Ordinance on Occupational Health Care (ArbMedVV)
BGV A1 Employer's Liability Insurance Association Regulation for Safety and Health at Work - Accident Prevention Regulation - Principles of Prevention

DGUV Rule 112-190 Employer's liability insurance association rules for safety and health at work - "Use of respiratory protective equipment"

Hazardous Substances Ordinance (GefStoffV) with associated Technical Rules for Hazardous Substances (TRGS), in particular TRGS 402
"Determination and assessment of hazards during activities involving hazardous substances: Inhalative exposure" and other technical rules for hazardous substances.

Order details:

Article number	Description
924715	Overpressure combination filter 86 ABEKHgSt with M 45x3
111204	Full face mask BRK 820 A
111704	Wall container for full face mask including one filter
111705	Wall container for two full face masks including two filters
111703	Carrying box B78 for one full face mask and one filter

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt