

BR-Article-No.: 201607

Item name: Airsafe 2303-C

Article Type: Personal Protective Equipment

Area of protection: Insulating respiratory protection

Usage: If you want to ensure the breathing air supply via a mobile breathing air supply, or a compressed air network / medium-pressure compressor, despite remote locations, the AIRSAFE 2203 - 2302 is ideal. The system does not require an external high-pressure supply. It can bridge large distances and supply two equipment carriers simultaneously. If the supply pressure falls below approx. 3.5 bar or suddenly fails, the system automatically switches to the integrated emergency air supply without interrupting the vital breathing air supply. An intermittent audible warning signal sounds.



## Technical data

External dimensions: 600 x 400 x 385mm

Case material: aluminum transport case with telescopic handle

Weight: approx. 19 kg

Pressure reducer: DM 600

Bottles: 2 x 2l - 300 bar composite (ca.1104 l breathing air)  
2 x 3l - 300 bar Composite (ca.1650 l breathing air)

Revision 02.2021 – Errors and omissions excepted. All data are non-binding guide values.

**BartelsRieger Atemschutztechnik GmbH**

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de

Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt