Datasheet Screw filter 86 AXSt



With Safety.

BR-Article-No.: 924702

Article-Name: 86 AXSt

Article-Type: Breathing protection screw filter. AX-P3 RD

Kind of Article: Combined filter acc. EN 14387:2008 filter class AX-P3 RD

for filtering device acc. EN 133 (Personal protective equipment)

Use: Connected to full face masks (EN 136) or a half mask (EN 140) with

standard thread connector. Single use only for respiratory protection against gases and vapours of low boiling organic compounds (boiling temp. < 65°C) and re-useable (R) against toxic and harmful particles, (D = storage test with Dolomite-particles acc. EN 143)

Description: Cylindrical housing with standard thread connector acc. EN 148-1

(outside thread Rd 40 x 1/7) to connect to a masks with inside

thread Rd 40 x 1/7

Materials: Filter housing, hole plate aluminium alloy

Clamp ring steel

Gas filter medium activated charcoal Particle filter medium glass-/cellulose fibre

Protection caps polyethylene

Measurements: Diameter approx. 108 mm, height approx. 100 mm

Weight: Approx. 290 grams

Inhalation resistance < 2,6 mbar at 30 L/min constant air flow

< 9.8 mbar at 95 L/min constant air flow

Marking: BARIKOS/BR-Logo Combined filter EN 14387:2008 AX-

P3 RD

+++ (charge-no.) yyyy/mm (expiry date) Typ 86 AXSt Art.-No. 924702 Colour marking: brown-white

Handling: Unseal the filter only directly before use (remove protection caps)

and screw it tight into the connector piece of the mask

Storage: Room temperature, protected against cold, heat and humidity

Warning advice: Follow instructions for use!

Revision 09.2016 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH