

Datasheet Breathing filter 85 AXSt

Designation: Breathing protection screw filter AX-P2 R D
Combination filter to DIN EN 14387 - filter type / filter class AX
P2 R D as part of a respiratory protective device to
DIN EN 133 - filter device

Description: Cylindrical housing with round thread connection according to
DIN EN 148-1 (external thread Rd 40 x 1/7)

Article-Number: 924602

Application: In conjunction with breathing connection - Full face masks (EN 136) or half
masks (EN 140) with round thread connection - Single use for protection
against gases and vapors of low-boiling organic compounds (boiling point \leq
65°C) and against harmful particles
R = Reusable - reusable against particles
D = particularly resistant to clogging by dust
(storage test with dolomite dust according to EN 143)

Standards: DIN EN 133 Respiratory protective devices - Classification
DIN EN 148-1 Respiratory protective devices - Threads for
breathing connections - Round thread
connection
DIN EN 14387 Respiratory protective devices - Gas filters
and combination filters

Identification colors: brown - white (adhesive label)

Materials: Housing, perforated disk Aluminum alloy
Lower perforated disk Polypropylene black
Filter medium Activated carbon and glass/cellulose fiber
Non-woven discs Polypropylene
Closure foil Polypropylene

Dimensions: Diameter approx. 108 mm
Height approx. 104 mm

Weight: approx. 290 grams

Inhalation resistance: < 2.1 mbar at 30 l/min constant air flow
< 8.0 mbar at 95 l/min constant air flow

Filter flow rate: Sodium chloride test at 95 l/min: < 6 %
Kerosene oil test at 95 l/min: < 6 %

Storability: 6 years - from date of manufacture (protected from cold, heat and moisture)

Handling: Only open the filter packaging immediately before use
and screw firmly into the connector of the mask.

Main application: Painting solvent vapors (boiling point \leq 65°C).

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.



Datasheet Breathing filter 85 AXSt

Service life:

The service life of combination filters depends on several factors such as concentration of harmful gases, ambient temperature, humidity, work severity, posture, etc. and therefore cannot be predicted. be determined in advance.

Application limits:

Opened filters must be replaced after 6 months at the latest. according to technical rules for hazardous substances TRGS 900 "Occupational exposure limits"

with half/quarter mask (gas filter):	30 times the occupational exposure limit value
with full face mask (gas filter):	400 times the occupational exposure limit value
with half/quarter mask (particle filter):	10 times the occupational exposure limit value
with full face mask (particle filter):	15 times the occupational exposure limit value

Maximum permissible Gas concentration: Type AX = 5,000ml/m³ (use limit for filter devices without fan and multiple use only within one work shift)

Maximum permissible Gas concentration: Type AX = 1,000ml/m³ (application limit for filter devices with blower and multiple use exclusively within one work shift)

Instructions for use:

The use of breathing filters requires a basic knowledge of the function and handling of respiratory protective devices. Information on this can be found in the trade association regulations and rules, in particular in DGUV Rule 112-190.

The use of breathing apparatus generally means additional stress for the person wearing the breathing apparatus.

Most respiratory protective devices require occupational health screening in accordance with the "Ordinance on Occupational Health Care" (ArbMedVV).

Damaged filters must not be used.

In ATEX areas, these respiratory protection filters can be used in potentially explosive atmospheres in zones 1, 21, 2 and 22 if the following requirements are observed:

- Respiratory protection filters must be earthed via a dissipative mask and via the earthing of the wearer with a leakage resistance <108 Ω.
- The respiratory protection filters must not be used in areas where highly charge-generating processes are to be expected.
- In the presence of an explosive atmosphere, the respiratory protection filters may only be worn on the face mask and not on the belt.
- The permissible ambient temperature must not exceed a value of 70 °C, assuming a temperature increase of 10 K at the parts in contact with an explosive atmosphere during normal operation and also in the event of a fault (zone 1 or 21) or during normal operation (zone 2 or 22) due to the activated carbon filter

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de

Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt

Datasheet Breathing filter 85 AXSt

Rules / regulations: Regulation (EU) 2016/425 on personal protective equipment
PPE Usage Ordinance (PSA-BV)
Ordinance on Occupational Health Care (ArbMedVV)
BGV A1 Employer's Liability Insurance Association Regulation for Safety and Health at Work - Accident Prevention Regulation - Principles of Prevention

DGUV Rule 112-190 Employer's liability insurance association rules for safety and health at work - "Use of respiratory protective devices"

Hazardous Substances Ordinance (GefStoffV) with associated Technical Rules for Hazardous Substances (TRGS), in particular TRGS 402
"Determination and assessment of hazards during activities involving hazardous substances: Inhalative exposure" and other technical rules for hazardous substances.

Order details:	Article number	Description
	924602	Combination filter 85 AXSt
	111200	Full face mask BRK 820
	111201	Full face mask BRK 820 V
	111208	Full face mask BRK 820 G
	111400	Full face mask TR 2002 CL3
	913503	Half mask 620 N
	913510	Half mask 620 S
	912500BL	Half mask 600
	111704	Wall container for full face mask including one filter
	111705	Wall container for two full face masks including two filters
	111703	Carrying case B78 for one full face mask and one filter

Revision 11.2023 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt