

Datasheet Airsafe 2303-C

Designation:	Mobile breathing air supply AirSafe 2303-C
Description:	High-pressure breathing air case with emergency air supply mounted in sturdy transport case
Article-Number:	201607
Materials:	Aluminum case with telescopic handle
Application:	<p>The AIRSAFE 2303 is ideal if you want to ensure the supply of breathing air via a mobile breathing air supply or a compressed air network / medium-pressure compressor despite remote locations. The system does not require an external high-pressure supply. It can bridge large distances and supply two equipment carriers simultaneously. If the supply pressure falls below or suddenly fails to reach approx. 3.5 bar, the system automatically switches to the integrated emergency air supply without interrupting the vital breathing air supply. An intermittent acoustic warning signal sounds.</p>
Dimensions:	600 x 400 x 385mm
Weight:	approx. 19kg
Breathing air supply:	Two 3l / 300 bar breathing air cylinders (approx. 1104 l breathing air)
Pressure reducer:	2 x DM 1900
Emergency air supply:	Has a high pressure control manometer and a warning whistle.



Revision 02.2024 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt