

Datasheet Unassisted fresh air hose breathing apparatus DUCT ECO

Designation:	Unassisted fresh air hose breathing apparatus DUCT ECO with belt set and breathing hose	
Description:	Unassisted fresh air hose breathing apparatus DUCT ECO is used with a full face mask. It is used in environments with a lack of oxygen and confined spaces such as tanks, silos, wells, sewage systems, etc. With the DUCT ECO, an unsupported fresh air breathing apparatus, only lung power is used for breathing.	
Article-Number:	202969	
Use:	DUCT is suitable for access in confined spaces.	
Standards:	DIN EN 138	Fresh-air breathing apparatus in conjunction with Full face mask, half mask or mouthpiece set
	DIN EN 148-1	Respiratory protective devices - Thread for breathing connections
Dimension:	Hose length	10 m
Weight:	Unassisted fresh air hose breathing apparatus	8.3 kg
	Hose 10 m	4.42 kg
Protection level:	1000	
Handling:	Carrying strap with adjustable hip belt, shoulder strap with Velcro fastener so that the breathing tube can be placed over the shoulders for carrying. Filter at the end of the hose prevents the ingress of foreign objects.	
Manufacturer:	Spasciani	
Storage:	Room temperature. Protect from cold, heat and moisture!	
Warning:	Several hoses can be coupled together. Maximum hose length = 20 meters	



Revision 04.2024 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de

Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt